

Recommended Maintenance Checklist

| Item to check | First operation | Daily | 25 hourly | Pre-season |
|---|-----------------|-------|-----------|------------|
| Hydraulic, hose and cylinders for damage and oil leaks | ✓ | ✓ | | ✓ |
| Airline leaks and hose damage | ✓ | ✓ | | ✓ |
| Loose or missing fasteners/split pins | ✓ | ✓ | | ✓ |
| Check bushes, pivot and cylinder pins for wear and replace as necessary | | | | ✓ |
| Swivel unit fasteners | ✓ | ✓ | | ✓ |
| Swivel unit - free and smooth rotation | | ✓ | ✓ | ✓ |
| Swivel unit temperature: Average operating temperature is 55 °C, Failure is indicated at +80 °C | ✓ | ✓ | | ✓ |
| Tyres are inflated to correct pressure | ✓ | ✓ | ✓ | ✓ |
| Wheel nuts are tightened at correct torque | ✓ | | | ✓ |
| Check wheel bearings | ✓ | ✓ | ✓ | ✓ |
| Check and tighten dust caps | ✓ | | ✓ | ✓ |
| Tow hitch bolts are tightened at correct torque | ✓ | | | ✓ |
| Disc roll pins/ locking bolts are in place | ✓ | | | ✓ |
| Chain is tensioned correctly | ✓ | ✓ | | ✓ |
| Lights are working correctly | ✓ | ✓ | | ✓ |
| Warning signs are attached | ✓ | ✓ | | ✓ |
| Grease wheel bearings | | | | ✓ |
| Grease wheel arm frame (2006 ONLY) | | | ✓ | ✓ |



| Item to check | First operation | Daily | 25 hourly | Pre-season |
|--|-----------------|-------|-----------|------------|
| Grease wheel lift bush (2006 ONLY) | | | ✓ | ✓ |
| Grease centre cylinder pins x 2 | | | ✓ | ✓ |
| Grease jockey wheel (3009NT and 4012 ONLY) | | | ✓ | ✓ |
| Grease wing chain tensioner threads (3009NT and 4012 ONLY) | | | ✓ | ✓ |
| Grease wing hinge pins x 8 | | | ✓ | ✓ |

We recommend that swivel units are covered during storage to prevent water penetration.

