

Recommended Maintenance Checklist

Item to check	First operation	Daily	25 hourly	Pre-season
Hydraulic, hose and cylinders for damage and oil leaks	✓	✓		✓
Airline leaks and hose damage	✓	✓		✓
Loose or missing fasteners/split pins	✓	✓		✓
Check bushes, pivot and cylinder pins for wear and replace as necessary				✓
Swivel unit fasteners	✓	✓		✓
Swivel unit - free and smooth rotation		✓	✓	✓
Swivel unit temperature: Average operating temperature is 55 °C, Failure is indicated at +80 °C	✓	✓		✓
Tyres are inflated to correct pressure	✓	✓	✓	✓
Wheel nuts are tightened at correct torque	✓			✓
Check wheel bearings	✓	✓	✓	✓
Check and tighten dust caps	✓		✓	✓
Tow hitch bolts are tightened at correct torque	✓			✓
Disc roll pins/ locking bolts are in place	✓			✓
Chain is tensioned correctly	✓	✓		✓
Lights are working correctly	✓	✓		✓
Warning signs are attached	✓	✓		✓
Grease wheel bearings				✓
Grease wheel arm frame (2006 ONLY)			✓	✓



Item to check	First operation	Daily	25 hourly	Pre-season
Grease wheel lift bush (2006 ONLY)			✓	✓
Grease centre cylinder pins x 2			✓	✓
Grease jockey wheel (3009NT and 4012 ONLY)			✓	✓
Grease wing chain tensioner threads (3009NT and 4012 ONLY)			✓	✓
Grease wing hinge pins x 8			✓	✓

We recommend that swivel units are covered during storage to prevent water penetration.

