

Thank you for choosing a Kelly Engineering product

We trust that you find the following manual clear and easy to follow. If you should require additional customer support or assistance, please do not hesitate to contact us.

Spare parts can be purchased, as required, through your local dealer or by contacting Kelly Engineering Australia or in the United States, Hood & Company.

Kelly Engineering welcomes feedback. Should you have any difficulties that you wish to raise, suggestions for improvement or modifications that you feel would enhance our products we look forward to hearing from you.

Australia Kelly Engineering

PO Box 100

Booleroo Centre SA 5482

Phone: + 61 8 8667 2253 **Fax:** + 61 8 8667 2250

Email: sales@kellyengineering.com.au **Spare Parts:** parts@kellyengineering.com.au **Website:** www.kellyengineering.com.au

United States Kelly Engineering

Website: www.kellyharrows.com

Spare Parts Hood & Company Inc Springfield MO

Phone: 417 865 2100 **Fax:** 417 865 2105

Email: hoodco@hoodco.com

Contents


Section 1: Unpacking	Page no 5
Section 2: Parts	8
Section 3: Decal Placement	119
Section 4: Chain Assembly	142
Section 5: Diagrams and Charts	152
Section 6: Operation	157



This symbol indicates which bag the relevant fastners are in



This symbol indicates which bag the relevant hydraulics are in




This symbol indicates which way the machine is travelling

Bolt Torque Settings

Bolt Type		Whee	el nut		U Bolt			Grade 8.8 Bolt			Grade 10.9 Bolt		Grade 8 Bolt		
Bolt Size	M18	M20	1/2"	9/16"	M10	M12	M16	M10	M12	M16	M20	M24	M20	M24	1"UNF
Ft lb	255	265	90	100	22	36	55	32	48	140	190	270	300	350	849
Nm	345	360	125	140	30	50	75	44	65	190	260	370	406	475	1151

[1] When fitting a wheel & tire to a hub, tighten the wheel nuts in a star pattern to the correct tension. To achieve this choose a wheel nut & tighten, then proceed to the opposite side of the hub to the next wheel nut & tighten & so on until all wheel nuts are tight. Then repeat the procedure to check that all nuts are tight. Do not use impact tools to tighten wheel nuts. For a guide to the correct tension of the wheel nuts please use the appropriate tension for your size wheel nuts from the Bolt Torque Settings table.

Torque values are for dry threads and surfaces however it is permissible to apply a small amount of anti corrosive oil to the threads.



Section 1 Unpacking

We recommend that a crane and forklift truck be available for unloading and assembly

Unpacking




• Before opening shipping container inspect exterior for any damage. Remove seal and open container doors.




CAUTION

Take care when opening doors as load may have shifted or restraints may have broken.

- Remove boxes from doorway of container one at a time using a forklift truck. Each box weighs approximately 2600 lbs (1200kg)
- Check strapping on each bundle before attempting to remove
- Attach chains to the packing frame using shackles and using suitable equipment (eg. fork-lift or tractor) drag framework bundles out of container. To move bundles away from front of container lift from side with forklift. Do not lift under angle iron frame, lift only under centre frame. Each bundle weighs approximately 7000 lb (3200 kg).











CAUTION

Before cutting straps attach slings or chains and take the weight of the frames to avoid them slipping or falling and causing injury.

CAUTION

Wear eye and hand protection when cutting straps. Sharp edges are exposed as straps separate and may cause injury.


CAUTION


To avoid falling or moving components, before cutting straps attach slings or chains to individual pieces and only cut the straps holding the piece to be lifted.

- Remove boxes from rear of container one at a time using a forklift truck. Each box weighs approximately 2600 lbs (1200 kg)
- Cut straps holding bundles and separate parts and place in assembly area
- Identify parts for each machine by serial no. or description and separate. Open parts box and check that all parts are accounted for against checklist
- Once all parts have been identified machines are ready for assembly
- Read assembly instructions before proceeding.


Section 2 Parts


Item No.	Description	Number	Qty
1	40' Centre Frame	0840-01	1
2	2.75"R 6 Tonne 8 on 8" PCD Hub & Stub Complete	0733-SH27596880	2
3	M20 x 170 grade 8.8 ZP Bolt	0211-20170	2
4	Nyloc Nut M20	0221-NYL20	2






Item No.	Description	Number	Qty
1	40' LH Inner Wing Frame	0840-05	1
2	PCH Wing Pivot Pin	0801-10-08-235	2
3	35 ID x 50mm DX Bush	0113-MB 3550DX	4
4	Grease Nipple 1/8" BSP 45 Deg	0181-GN1-845	2
5	Cotter Pin M13 x 63	0261-PINC1363	2
6	M12 x 65 grade 8.8 ZP Bolt	0211-1265	2
7	Nyloc Nut M12	0221-NYL12	2







Item No.	Description	Number	Qty
1	40' LH Outer Wing Frame	0840-07	1
2	35 ID x 50mm DX Bush	0113-MB 3550DX	4
3	Grease Nipple 1/8" BSP 45 Deg	0181-GN1-845	2
4	PCH Wing Pivot Pin	0801-10-08-235	2
5	Cotter Pin M13 x 63	0261-PINC1363	2
6	Nyloc Nut M12	0221-NYL12	2
7	M12 x 65 grade 8.8 ZP Bolt	0211-1265	2







Item No.	Description	Number	Qty
1	40' RH Inner Wing Frame	0840-04	1
2	35 ID x 50mm DX Bush	0113-MB 3550DX	4
3	Grease Nipple 1/8" BSP 45 Deg	0181-GN1-845	2
4	PCH Wing Pivot Pin	0801-10-08-235	2
5	Cotter Pin M13 x 63	0261-PINC1363	2
6	M12 x 65 grade 8.8 ZP Bolt	0211-1265	2
7	Nyloc Nut M12	0221-NYL12	2







Item No.	Description	Number	Qty
1	40' RH Outer Wing Frame	0840-06	1
2	35 ID x 50mm DX Bush	0113-MB 3550DX	4
3	Grease Nipple 1/8" BSP 45 Deg	0181-GN1-845	2
4	PCH Wing Pivot Pin	0801-10-08-235	2
5	Cotter Pin M13 x 63	0261-PINC1363	2
6	M12 x 65 grade 8.8 ZP Bolt	0211-1265	2
7	Nyloc Nut M12	0221-NYL12	2






Item No.	Description	Number	Qty
1	40' Inner Wing Post	0840-04P	1
2	M12 x 50 grade 8.8 ZP Bolt	0211-1250	6
3	Nyloc Nut M12	0221-NYL12	6






Item No.	Description	Number	Qty
1	40' Outer Wing Post	0840-06P	1
2	M12 x 40 grade 8.8 ZP Bolt	0211-1240	4
3	Nyloc Nut M12	0221-NYL12	4







Item No.	Description	Number	Qty
1	Dual Circuit 3 Stage Sequence Manifold V12	0802-691033	1
2	M10 x 25 grade 8.8 ZP Bolt	0211-1025	6
3	Washer Flat M10	0231-F10	6
4	Washer Spring M10	0231-S10	6









Item No.	Description	Number	Qty
1	5" Bore 30" Stroke 3 1/8" S/Tube 2" Rod Hydraulic Cylinder	0311-530ST	1










Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elbow	0323-S91-1212	2












Item No.	Description	Number	Qty
1	Double Clamp Bolt Group 2	0325-RCD-2BH	1
2	Clamp top plate group 2	0325-RCD-2PT	1
3	17mm Clamp Jaws (Pair)	0325-RCD-17J	2
4	Double Clamp Stacking Plate (Non Ryco)	0325-SI-2-5D-W3	1
5	Double Clamp Stacking Bolt Group 2	0325-RCD-2BS	1



Item No.	Description	Number	Qty
1	5" Bore 30" Stroke 3 1/8" S/Tube 2" Rod Hydraulic Cylinder	0311-530ST	1








Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elbow	0323-S91-1212	2








Item No.	Description	Number	Qty
1	Right CR Port to RH Main Wing Cylinder Retract Port	PH40-06R	1
2	Right CE Port to RH Main Wing Cylinder Extend Port	PH40-07R	1









Item No.	Description	Number	Qty
1	3" Bore x 24" Stroke 1.5" Rod Hydraulic Cylinder	0311-324	2








Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elbow	0323-S91-1212	4






Item No.	Description	Number	Qty
1	LR port to LH Wing Retract Tee	PH40-08L	1
2	LE Port to LH Wing Extend Tee	PH40-09L	1
3	3/4" JIC Male Tee 3/4" JIC Male Tee 3/4" JIC Male Tee	0324-S19-121212	2
4	3/4" JIC Male 3/4" JIC Female Swivel 90° Elbow	0323-S15-1212	1









Item No.	Description	Number	Qty
1	LH Wing Extend Tee to Rear LH Outer Wing Cylinder Extend Port	PH40-12	1
2	LH Wing Retract Tee to Rear LH Outer Wing Cylinder Retract Port	PH40-13	1












Item No.	Description	Number	Qty
1	4" Bore 24" Stroke 1.75" Rod Hydraulic Cylinder	0311-424	1








Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elbow	0323-S91-1212	2










Item No.	Description	Number	Qty
1	RR Port to RH Outer Wing Cylinder Retract Port	PH40-08R	1
2	RE Port to RH Outer Wing Cylinder Extend Port	PH40-09R	1


























Item No.	Description	Number	Qty
1	40' Front A Frame	0840-02	1
2	M24 x 75 grade 8.8 zp Bolt	0211-2475	12
3	Nyloc Nut M24	0221-NYL24	12









Item No.	Description	Number	Qty
1	2.75"R 6 Tonne 8 on 8" PCD Hub & Stub Complete	0733-SH27596880	1
2	M20 x 170 grade 8.8 ZP Bolt	0211-20170	1
3	Nyloc Nut M20	0221-NYL20	1






Item No.	Description	Number	Qty
1	2.75"R 6 Tonne 8 on 8" PCD Hub & Stub Complete	0733-SH27596880	1
2	M20 x 170 grade 8.8 ZP Bolt	0211-20170	1
3	Nyloc Nut M20	0221-NYL20	1








Item No.	Description	Number	Qty
1	15.0/70-18 Tyre On 8 on 8" PCD Rim	0751-15.0-70-18TR	4







All wheel nuts tightened to 100fl-lb / 140Nm




Signed_____ Date___/__/__ Unit Serial Number:____


Item No.	Description	Number	Qty
1	T-Bar Drawbar	1510-08	1
2	Drawbar Pivot Pin	0801-10-13-970	1
3	Drawbar Pivot Bush	0801-B423838	4
4	M12 x 65 grade 8.8 ZP Bolt	0211-1265	1
5	Nyloc Nut M12	0221-NYL12	1
6	Cotter Pin M13 x 63	0261-PINC1363	1







Item No.	Description	Number	Qty
1	Tow Hitch	0810-09	1
2	Drawbar Tow Hitch Pin	1601-P35-370	1
3	M12 x 75 grade 8.8 ZP Bolt	0211-1275	1
4	Nyloc Nut M12	0221-NYL12	1
5	Cotter Pin M13 x 63	0261-PINC1363	1
6	Hardened Tow Hitch Bush 2 1/4"	0801-KE-0905-1-B	1
7	Criclip External 82mm	0172-D1400-0820	1







Item No.	Description	Number	Qty
1	Parallel Arm	0810-22	1
2	Clevis Pin 25mm x 75mm	0801-KE0307-1	2
3	Washer Flat M24	0231-F24	2
4	Cotter Pin M6 x 50mm	0261-PINC650	2







Item No.	Description	Number	Qty
1	3" Bore x 12" Stroke 1.5" Rod Extended Hydraulic Cylinder	0311-312EXT	1






Item No.	Description	Number	Qty
1	Jack Assembly	0801-SAK45B	1
2	Jack Pin	0801-B3077	1








Item No.	Description	Number	Qty
1	Hose Post Spring	1601-CDB-00-0012	1
2	M16 x 35 grade 8.8 zp Bolt	0211-1635	1
3	Washer Spring M16	0231-S16	1
4	Washer Flat M16	0231-F16	1
















Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elbow	0323-591-1212	2













Item No.	Description	Number	Qty
1	40' Rear A Frame	0840-03	1
2	Tail Frame Pivot pin	0801-10-08-175	2
3	M12 x 65 grade 8.8 ZP Bolt	0211-1265	2
4	Nyloc Nut M12	0221-NYL12	2
5	Cotter Pin M13 x 63	0261-PINC1363	2





Item No.	Description	Number	Qty
1	70mm Jockey Wheel	0810-11-70	1
2	Plain Spherical Bearing 70mm	0113-GE70DO-2RS	2
3	Circlip Internal 105mm	0171-J105	2
4	Circlip External 70mm	0172-D1400-70	1
5	Grease Nipple 1/4" UNF	0181-GN1-4	2







Circlip fitted to jockey Wheel shaft
Signed_____ Date___/__/
Unit Serial Number:______



Item No.	Description	Number	Qty
1	Brake Disc	1600-405	1
2	M12 x 24 Wheel Bolt	0216-WB1224	3
3	Bolt on Brake Disc Dust Cap 70 ID x 135 OD x 35	1601-DC7013535	1






Wheel bolts torqued to 65ft-lb / 88nm


Signed_____ Date__ /__ /__
Unit Serial Number:_____



Item No.	Description	Number	Qty
1	Jockey Wheel Brake Caliper	0810-12CAL	9
2	Brake Compression Spring	0801-KE009	1
3	Washer Square M16 x 50 x 5	0231-SQ16505	1
4	M16 x 150 grade 8.8 zp Bolt	0211-16150	2
5	Nyloc Nut M16	0221-NYL16	1








Check tension of brake caliper spring (50-63mm road transport)




Signed	Date / /
Signed_ Unit Serial Number:_	

Item No.	Description	Number	Qty
1	Axle 2"R 3T 6 on 6" PCD 330 OHF	0733-K5083T66S	2
2	M16 x 90 grade 8.8 zp Bolt	0211-1690	2
3	Nyloc Nut M16	0221-NYL16	2











Item No.	Description Number		Qty
1	11L15 F3 Tyre on 6 on 6" Stud Rim	0751-11L15	2







All wheel nuts tightened to 90ft-lb / 125nm




Signed	Date	1 1
Signed_ Unit Serial Number:		


Item No.	Description	Number	Qty
1	Extended Tip Rear Tail	0810-10E	1
2	Tail Frame Pivot pin	0801-10-08-175	2
3	M12 x 65 grade 8.8 ZP Bolt	0211-1265	2
4	Nyloc Nut M12	0221-NYL12	2
5	Cotter Pin M13 x 63	0261-PINC1363	2





Item No.	Description	Number	Qty
1	3.5" Bore 24" Stroke 1.75" Rod Hydraulic Cylinder	0311-3524SP	2








Item No.	Description	Number	Qty	1
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elb	ow 0323-S91-1212	4	M
			Вох	
			76.	
		1	1	
			1	1
			(SOUTH	S S
			1 00	6
	2)	3		
	(R 08)	17		
		6210	W.	
17.		111		X
7 ,		1111		1911
~	· The state of the	13.8311		7
	MILL A SELLIN	3 ()		
	of sold the	V 7 64		
	Mr.	TO THE		
		1	0	
		12/	1///	
		City Company	1.	
- 1		1	. /	
		000	/	
()				
1				
1				


Item No.	Description	Number	Qty
1	TE1 Port to Tail Extend Tee	PH40-04	1
2	TR1 Port to Tail Retract Tee	PH40-05	1
3	3/4" JIC Male Tee 3/4" JIC Male Tee 3/4" JIC Male Tee	0324-S19-121212	2










Item No.	Description	Number	Qty
1	Tail Lift Extend Tee to LH Tail Lift Extend Port	PH40-20	1
2	Tail Lift Retract Tee to LH Tail Lift Cylinder Retract Port	PH40-21	1






Item No.	Description	Number	Qty
1	Tail Lift Extend Tee to RH Tail Lift Cylinder Extend Port	PH40-22	1
2	Tail Lift Retract Tee to RH Tail Lift Cylinder Retract Port	PH40-23	1







Item No.	Description	Number	Qty
1	Extended Tip Tail Bolt On Tip	0810-10ET	1
2	M16 x 50 grade 8.8 zp Bolt	0211-1650	10
3	Nyloc Nut M16	0221-NYL16	10
4	Washer Flat M16	0231-F16	20










Item No.	Description	Number	Qty
1	40' Front Module	0810-28-40	1
2	M16 x 45 grade 8.8 zp Bolt	0211-1645	8
3	Nyloc Nut M16	0221-NYL16	8








Item No.	Description	Number	Qty
1	LH Dropleg No Clevis	0810-24F	1
2	RH Dropleg No Clevis	0810-25F	1
3	LH Chain Adjusting Lug	0810-26	1
4	RH Chain Adjusting Lug	0810-27	1
5	Forged Clevis 21mm Bolt Hole	0801-FC21	2
6	Stainless Steel Wear Bush	1501-365033-SS	2
7	M24 x 140 grade 8.8 zp Bolt	0211-24140	2
8	Nyloc Nut M24	0221-NYL24	2
9	M36 x 105 grade 8.8 zp Bolt	0211-36105	2
10	Nyloc Nut M36	0221-NYL36	2






Item No.	Description	Number	Qty
1	Cast 25mm Spacing	0801-CS25	16
2	M10 x 30 grade 8.8 ZP Bolt	0211-1030	16
3	Nyloc Nut M10	0221-NYL10	16









Item No.	Description	Number	Qty
1	Chain Tension Adjustor	0802-PCHTA	2
2	Washer High Tensile 1 1/4"	0232-HT11-4	2
3	20mm Compression Spring	0801-XK9261S	2
4	Tensioner Cup - Male	0801-KE0805-3	2
5	Female Spring Locator	0801-KE0805-4	2












em No.			
itelli ivo.	Description	Number	Qty
1	Cast 25mm Spacing	0801-CS25	16
2	M10 x 30 grade 8.8 ZP Bolt		
3			16
2 3	M10 x 30 grade 8.8 ZP Bolt Nyloc Nut M10	0221-NYL10	16 16
			4

Item No.	Description	Number	Qty
1	Chain Tension Adjustor	0802-PCHTA	2
2	Washer High Tensile 1 1/4"	0232-HT11-4	2
3	20mm Compression Spring	0801-XK9261S	2
4	Tensioner Cup - Male	0801-KE0805-3	2
5	Female Spring Locator	0801-KE0805-4	2













Item No.	Description	Number	Qty
1	Standard Chain Mount Plate	0810-20	1
2	Forged Clevis 21mm Bolt Hole	0801-FC21	1
3	Height Adjusting Chain Assembly	0801-20MCA	1
4	Stainless Steel Wear Bush	1501-365033-SS	1
5	Chain Mount Pivot Pin	0801-10-51	1
6	Washer High Tensile 1 3/8"	0232-HT13-8	1
7	M36 x 105 grade 8.8 zp Bolt	0211-36105	1
8	M12 x 65 grade 8.8 ZP Bolt	0211-1265	1
9	Nyloc Nut M36	0221-NYL36	1
10	Nyloc Nut M12	0221-NYL12	1
11	Height Adjustor Retaining Clip	0801-KE014	1







Item No.	Description	Number	Qty
1	Extended Chain Mount Plate	0810-21	1
2	Forged Clevis 21mm Bolt Hole	0801-FC21	1
3	Height Adjusting Chain Assembly	0801-20MCA	1
4	Stainless Steel Wear Bush	1501-365033-SS	1
5	Chain Mount Pivot Pin	0801-10-51	1
6	M36 x 105 grade 8.8 zp Bolt	0211-36105	1
7	Nyloc Nut M36	0221-NYL36	1
8	Washer High Tensile 1 3/8"	0232-HT13-8	1
9	M12 x 65 grade 8.8 ZP Bolt	0211-1265	1
10	Nyloc Nut M12	0221-NYL12	1
11	Height Adjustor Retaining Clip	0801-KE014	1












Item No.	Description	Number	Qty
1	Rear Module Tension Body	0810-103R	1
2	Module Tension Rod Assembly	0810-105A	1
3	20mm Compression Spring	0801-XK9261S	1
4	Rigid Spring Locator	0801-10-S2L	1
5	Height Adjusting Chain Assembly	0801-20MCA	1
6	Washer High Tensile 1 1/4"	0232-HT11-4	1
7	Washer Flat M24	0231-F24	1










Item No.	Description	Number	Qty
1	Module Tension Arm	0810-104F	1
2	35 ID x 50mm DU Bush	0113-MB 3550DU	2
3	Forged Clevis 21mm Bolt Hole	0801-FC21	1
4	Module Pivot Arm Bush	0801-10-110	1
5	Stainless Steel Wear Bush	1501-365033-SS	1
6	M20 x 150 grade 8.8 ZP Bolt	0211-20150	1
7	Nyloc Nut M20	0221-NYL20	1
8	M36 x 105 grade 8.8 zp Bolt	0211-36105	1
9	Nyloc Nut M36	0221-NYL36	1







Item No.	Description	Number	Qty
1	Chain Mount Pivot Pin	0801-10-51	1
2	Washer High Tensile 1 3/8"	0232-HT13-8	1
3	M12 x 65 grade 8.8 ZP Bolt	0211-1265	1
4	Nyloc Nut M12	0221-NYL12	1
5	Height Adjustor Retaining Clip	0801-KE014	1







Item No.	Description	Number	Qty
1	Front Module Tension Body	0810-103F	1
2	Module Tension Rod Assembly	0810-105A	1
3	20mm Compression Spring	0801-XK9261S	1
4	Rigid Spring Locator	0801-10-S2L	1
5	Washer High Tensile 1 1/4"	0232-HT11-4	1
6	Height Adjusting Chain Assembly	0801-20MCA	1
7	Washer Flat M24	0231-F24	1






Item No.	Description	Number	Qty
1	Module Tension Arm	0810-104F	1
2	35 ID x 50mm DU Bush	0113-MB 3550DU	2
3	Module Pivot Arm Bush	0801-10-110	1
4	Forged Clevis 21mm Bolt Hole	0801-FC21	1
5	Stainless Steel Wear Bush	1501-365033-SS	1
6	M20 x 150 grade 8.8 ZP Bolt	0211-20150	1
7	Nyloc Nut M20	0221-NYL20	1
8	M36 x 105 grade 8.8 zp Bolt	0211-36105	1
9	Nyloc Nut M36	0221-NYL36	1







Item No.	Description	Number	Qty
1	Chain Mount Pivot Pin	0801-10-51	1
2	Washer High Tensile 1 3/8"	0232-HT13-8	1
3	M12 x 65 grade 8.8 ZP Bolt	0211-1265	1
4	Nyloc Nut M12	0221-NYL12	1





Item No.	Description	Number	Qty
1	30' Module Lift Plate	0810-106	1
2	Clevis Pin 25mm x 75mm	0801-KE0307-1	1
3	Height Adjustor Retaining Clip	0801-KE014	1
4	Washer Flat M24	0231-F24	1
5	Cotter Pin M5 x 50	0261-PINC550	1















Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 45° Elbow	0323-S88-1212	2







Item No.	Description	Number	Qty
1	ME2 Port to Front Module Lift Cylinder Extend Port	PH40-14	1
2	MR2 Port to Front Module Lift Cylinder Retract Port	PH40-15	1







Item No.	Description	Number	Qty
1	30' Module Lift Plate	0810-106	1
2	Clevis Pin 25mm x 75mm	0801-KE0307-1	1
3	Washer Flat M24	0231-F24	1
4	Height Adjustor Retaining Clip	0801-KE014	1
5	Cotter Pin M5 x 50	0261-PINC550	1






Item No.	Description	Number	Qty
1	2.5" Bore x 6" Stroke 1.5" Rod Side Port Cylinder	0311-256SP	1









Item No.	Description	Number	Qty
1	3/4" JIC Male 3/4" UN O Ring Male 90° Elbow	0323-S91-1212	2









Item No.	Description	Number	Qty
1	30' Module Lift Plate	0810-106	1
2	Clevis Pin 25mm x 75mm	0801-KE0307-1	1
3	Height Adjustor Retaining Clip	0801-KE014	1
4	Cotter Pin M5 x 50	0261-PINC550	1
5	Washer Flat M24	0231-F24	1









Item No.	Description	Number	Qty
1	2.5" Bore x 6" Stroke 1.5" Rod Side Port Cylinder	0311-256SP	1


















Item No.	Description	Number	Qty
1	Rear Module Extend Tee to LH Module Lift Cylinder Extend Port	PH40-18	1
2	Rear Module Retract Tee to LH Module Lift Cylinder Retract Port	PH40-19	1







Item No.	Description	Number	Qty
1	Rear Module Retract Tee to Right Rear Module Lift Cylinder Retract Port	PH40-16	1
2	Rear Module Extend Tee to Right Rear Module Lift Cylinder Extend Port	PH40-17	1



Item No.	Description	Number	Qty
1	40' Chain Carrier Beam	0810-17-40	1
2	Chain Carrier Mount Plate	0800-139.1	2
3	U-Bolt M16 x 112 Deep x 104 Wide	0271-16112104	4
4	U-Bolt M16 x 160 Deep x 127 Wide	0271-16160127	4
5	Washer Flat M16	0231-F16	16
6	Nyloc Nut M16	0221-NYL16	16










Item No.	Description	Number	Qty
1	Chain Carrier Bolt on End	0810-17L	2
2	M12 x 40 Coach Head Bolt	0215-CH1240	8
3	Washer Flat M12	0231-F12	8
4	Nyloc Nut M12	0221-NYL12	8










Item No.	Description	Number	Qty
1	40' Chain Carrier Beam	0810-17-40	1
2	Chain Carrier Mount Plate	0800-139.1	2
3	U-Bolt M16 x 85 Deep X 77 Wide	0271-168577	4
4	U-Bolt M16 x 160 Deep x 127 Wide	0271-16160127	4
5	Washer Flat M16	0231-F16	16
6	Nyloc Nut M16	0221-NYL16	16






Item No.	Description	Number	Qty
1	Chain Carrier Bolt on End	0810-17L	2
2	M12 x 40 Coach Head Bolt	0215-CH1240	8
3	Washer Flat M12	0231-F12	8
4	Nyloc Nut M12	0221-NYL12	8







Item No.	Description	Number	Qty
1	Outrigger	0810-109	2
2	M16 x 50 grade 8.8 zp Bolt	0211-1650	8
3	Nyloc Nut M16	0221-NYL16	8
(Q Q		









Item No.	Description	Number	Qty
1	Chain Carrier Bolt on End	0810-17L	2
2	M12 x 40 Coach Head Bolt	0215-CH1240	8
3	Washer Flat M12	0231-F12	8
4	Nyloc Nut M12	0221-NYL12	8







Item No.	Description	Number	Qty
1	Right Hand Off Set M	0810-18R	1
2	Left Hand Off Set M	0810-19L	1
3	U-Bolt M12 x 107 Deep x 106 Wide	0271-12105104	4
4	Round Tube Insert 60.3 x 3.2-5mm	0264-RTRi-5584	4
5	Washer Flat M12	0231-F12	8
6	Nyloc Nut M12	0221-NYL12	8










Item No.	Description	Number	Qty
1	Right Hand Off Set M	0810-18R	1
2	Left Hand Off Set M	0810-19L	1
3	Straight Chain Carrier M	0810-19	1
4	Round Tube Insert 60.3 x 3.2-5mm	0264-RTRi-5584	6
5	U-Bolt M12 x 80 Deep x 77 Wide	0271-128077	4
6	U-Bolt M12 x 157 Deep x 79 Wide	0271-1215577	2
7	Washer Flat M12	0231-F12	12
8	Nyloc Nut M12	0221-NYL12	12












Item No.	Description	Number	Qty
1	Rear Tail Guard	0800-235	2
2	Tail Chain Stop Guard	0800-220.1	1
3	Angled Chain Gaurd	0800-498	1
4	U-Bolt M12 x 157 Deep x 79 Wide	0271-1215577	8
5	Washer Flat M12	0231-F12	16
6	Nyloc Nut M12	0221-NYL12	16













Item No.	Description	Number	Qty
1	Safety Chain Assembly	0810-16	1







Item No.	Description	Number	Qty
1	Operator Manual Cannister	0801-OMC-1	1
2	Ratcheting Gear Wrench 1 3/4"	0802-GW1 3-4	1
3	20mm Bolt Swivel Unit	0802-PCHB55	1
4	M20 x 110 grade 10.9 ZP Short Thread Bolt	0211-20110ST	1
5	Nyloc Nut M20	0221-NYL20	1
6	M6 x 20 Trilobe self tapping Scew	0211-M620MZPHTF	3







Item No.	Description	Number	Qty
1	Cylinder Safety Stop	0800-212.1	1
2	Square Loop Pin M8 x 63	0511-PINLOOPSQ863	1










Item No.	Description	Number	Qty
1	20mm Bolt Swivel Unit	0802-PCHB55	1
2	Disc Chain Tie Plate Link 20mm	0802-DCTP-20	1
3	Tie Plate Bush	0801-PCDCS55	1
4	M20 x 110 grade 10.9 ZP Short Thread Bolt	0211-20110ST	3
5	Nyloc Nut M20	0221-NYL20	3











Section 3 Decal Placement













Item No.	Description	Number	Qty
1	Diamond Harrow 40 Decal	0801-SKDH40	1






Item No.	Description	Number	Qty
1	Diamond Harrow 40 Decal	0801-SKDH40	1







Item No.	Description	Number	Qty
1	Yellow Reflective Decal	0801-SYRF	1
2	Danger Crush Hazard Decal	0801-S3	1
3	Grease Decal	0801-S10	2










Item No.	Description	Number	Qty
1	Chain Tension 330mm Decal	0801-S15	1
2	Yellow Reflective Decal	0801-SYRF	2











Item No.	Description	Number	Qty
1	Grease Decal	0801-S10	5
2	Brake Caliper Decal	0801-S11	1




Item No.	Description	Number	Qty
1	Yellow Reflective Decal	0801-SYRF	1








Item No.	Description	Number	Qty
1	Yellow Reflective Decal	0801-SYRF	1













Item No.	Description	Number	Qty
1	Chain Tension 330mm Decal	0801-S15	1
2	Yellow Reflective Decal	0801-SYRF	1







Item No.	Description	Number	Qty
1	Danger Crush Hazard Decal	0801-S3	1
2	Yellow Reflective Decal	0801-SYRF	1
3	Grease Decal	0801-S10	2




Item No.	Description	Number	Qty
1	Yellow Reflective Decal	0801-SYRF	1







Item No.	Description	Number	Qty
1	Wheel Nut Decal	0801-S9	4
2	Decal, 15.0/70/18 Tyre Inflation	0801-S8-15.5-70-18	4




Item No.	Description	Number	Qty
1	Decal, 11L-15 Tyre Inflation	0801-S8-11L-15.JPG	2
2	Wheel Nut Decal	0801-S9	2







Section 4Chain Assembly




Item No.	Description	Number	Qty
1	Nyloc Nut M20/24	0221-NYL20/24	4
2	M20 x 110 / M24 x 120 grade 10.9 ZP Short Thread Bolt	0211-20110ST/0211-24120ST	4
3	20/24mm Bolt Swivel Unit	0802-PCHB55 / 0802-PCHB553	2
4	Disc Chain Tie Plate Link 20mm / 24mm	0802-DCTP-20 / 0802-DCTP-24	2
5	Tie Plate Bush	0801-PCDCS55	2
6	Roll Pin Zinc Plated 3/8" x 3"	0262-3-8X3	1
7	CL1-B Chain Disc Link	0803-CL1	1







Fitting Cast Link Pins


Please install cast link retaining Pins (3/8" x 3" Roll Pin, part number 0262-3-8X3) on all cast disc links. Failure to do this could lead to the discs becoming dislodged during transport causing severe damage or injury.




Item No.	Description	Number	Qty
1	0803-CL2-Link Assembly	0803-CL2	1
2	CL1-B Chain Disc Link	0803-CL1	1










Item No.	Description	Number	Qty
1	R300 Chain Link	0803-R300	1







Item No. Description		Number	Qty
1	W36/25 Chain Link	0803-W36	1







Item No.	Description	Number	Qty
1	10 Spike Disc Chain 49/27/5	0803-SD49	1
2	Tie Plate For 20mm Bolt/ Tie Plate For 24mm Bolt	0800-83.2 / 0800-83.3	4






Item No.	Description	Number	Qty
1	Prickle Chain Link	0803-PCH	1







Section 5Diagrams and Charts



Please ensure to bend tabs up and feed wire through, so the light cable is secure





Operating speeds

Operating speeds for normal conditions		
Chain type	Speed	
Prickle Chain	6-10 Mph / 10-16 kmph	
Disc Mulch Chain	6-8 Mph / 10-12 kmph	
Transport / towing on roads	15 Mph / 25 kmph	

Tire pressure

Tire size	Ply	PSI	KPA
16.5L x 16.1	14	36	250
H40 x 14.5-19	26	60	410
11L - 15	10	44	300
15.5/80/24	16	58	400
16.5/85/24	16	55	380
550/60/22.5	16	40	280
400/60/22.5	16	50	350
12.5/80/18	14	85	590
15.0/70/18	14	71	490

Chain Harrow specifications

Model	40′/12m
Working width	43'4"/13.2m
Transport width	11'6"/3.5m
Transport height	12′2″/3.7m
Transport length	52'6"/14.3m

Specifications

Disc Chain lengths

Mod	el 40ft	Length	CL2	CL1	W36	R300	SD49	Prickle chain
			CL2 disc chain also requires CL1 disc chain					
40′	Front right	25′/7.6m	CL2 - 32 CL1 - 2	46	46	60	60	84
	Front left	25′/7.6m	CL2 -32 CL1 - 2	46	46	60	60	84
	Rear right	29.8′/9.1m	CL2 - 32 CL1 - 14	57	60	79	79	109
	Rear left	25′/7.6m	CL2 - 33 CL1 - 2	45	47	62	62	87
	Modules front	8.9′/2.7m	CL2 - 10 CL1 - 2	17	17	22	22	31
	Modules rear	8.9′/2.7m	CL2 - 11 CL1 - 2	16	17	22	22	31

Section 6 Operation

Basic Operation

Unfolding:

- 1. Walk around and inspect the machine.
 - a. Check that chains are not hooked on framework
 - b. Check swivel bolts are in place and not broken
 - c. Check th at height adjusting chains have not fallen out of their slotted plates during transport.
 - d.Ensure front lift cylinder depth stops are fully engaged on cylinder shaft.
- 2. Lower front A frame to working height.
- 3. Unfold wings holding the hydraulic lever until both the main center cylinder pins have centered in their slots. (If chain pulls tight during unfold, stop and inspect if chain is hooked)
- 4. Lower rear tail by holding hydraulic lever until tail and modules are completely lowered to working position.
- 5. Walk around and check that all chain links are straight and that working height of all swivels is correct for field conditions. Adjust if neccessary.
- 6. Move off with all chains in working position. If neccessary it is acceptabe to raise front A pull to transport height. This will lift the front chains off the ground and reduce the load on the tractor. Lower the front A pull once moving satisfactorily.

Folding:

- 1. Lower the front A frame to working height. (This is important to ensure that all chains locate correctly in their transport rests).
- 2. Raise the Rear Tail and modules by holding the hydraulic lever until they come to a complete stop.
- 3. Fold the wings. They should move as follows; main center cylinders will retract, one or both, until the wings stand vertically. The left outer wing then the right outer wing will fold down.
- 4. Raise front A frame to transport height.
- 5. Walk around and check that chains have located correctly in transport rests. (30' only, close wing transport lock valves).

Setting for correct chain tension

Wings

Use the spanner supplied. Loosen the lock nut adjacent to the tensioner assembly body. Turn the tension bolt clockwise to compress the coil spring. Correct tension is acheived when spring retains its set length when operator rolls the chain fore and aft on the ground.

Retighten the lock nut.

See table below

Spring Compression Length

Model	inches	mm
40	12.4	330

When less than 4" (100mm) of thread remains visible on the adjustor bolt then a link must be removed from the chain









Modules

Loosen the lock nut on the draw bolt.

Tighten the adjusting nut clockwise until the outer face of the spring retaining washer is flush with the body of the module tensioning unit.

Retighten the lock nut.

If more than 8" (200mm) of thread is exposed then a link should be removed to maintain correct adjustment.





Importance of chain tension

Operational

It is imperative that the correct adjustment be maintained. Only through correct adjustment can a smooth and level finish be achieved in field working.

Loose chains lead to:

- Uneven performance across the width of the machine
- Uneven weed control
- Unsatisfactory incorporation
- Ineffective levelling
- Accelerated or premature chain wear
- Chains failing to engage with transport locators when folded
- Machine damage when folding or unfolding
- Uneven field surface with ridges and furrows being created. The leading 1/3rd of a loose chain is much more aggressive than the trailing 1/3rd and the center. This will mean that middle of the machine's front pair of chains will aggressively move soil outwards. The machine's rear pair of chains, if loose, have their aggressive 1/3rd near the wing extremity. It follows then that as the front discs push soil outwards, the least aggressive portion of the rear chain follows them and does not balance the soil movement. This is exacerbated at the wings, effectively creating a broad ridge about halfway out each wing. It won't be evident in one pass, but is possible if care is not taken over time.

A correctly adjusted machine will not cause this phenomenon.

Settings for correct working height

To adjust the swivel height at the wings, relocate one of the polyurethane spacers either above or below the fixed mounting tube.

Adjustment

1	Loosen chain tension completely
2	Undo 2 x M10 bolts from corresponding spacer set and take the two halfs off of the drop leg tube
3	Replace it in the selected position after raising or lowering the drop leg
4	Reinstall the M10 bolts and re-tension the chain

It is possible to install all spacers either above or below the mounting tube giving a maximum of 4"(100mm) of adjustment.





